




GSR225



Trucks & Commercial Light Trucks, All Position








Regional



Urban | Light Duty

Regional All Position Tire

Features	Benefits
 <p>Four belt construction</p>	Increases casing and tread stiffness, minimizing tire deformation for longer wear
 <p>Specially formulated tread compound</p>	Improved tread wear resistance and handling characteristics
 <p>Resilient and proven four groove tread design</p>	Provides consistent handling and vehicle control
 <p>Optimized sipe design on rib edges</p>	Improved wet traction and minimized irregular wear
 <p>New, improved bead construction</p>	Improved bead design for easier rim mounting

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
225/70R19.5	100EV656Q	14	G	128/126 L	6.75	6.00	3,970@110	3,750@110	8.9	14.9	31.9	16	651	70
245/70R19.5	100EV664Q	16	H	136/134 M	7.50	6.75	4,940@120	4,675@120	9.8	15.3	33.0	17	630	77
265/70R19.5	100EV1461Q	16	H	140/138 M	7.50	8.25	5,510@120	5,205@120	10.4	15.9	34.1	18	609	86
275/70R22.5	100EV776Q	16	H	148/145 M (152/148 J)	8.25	9.00	6,945@130	6,395@130	10.9	17.5	37.7	19	551	111
315/80R22.5	100EV1980Q	20	L	158/150 L (154/150 M)	9.00	9.75	9,370@131	7,390@120	12.3	19.7	42.4	22	490	149

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile
 Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES