



GDR652







For Trucks, Drive Position



Regional

Regional Deep Lug Drive Tire

Features	Benefits
 <p>Wide and deeper tread pattern</p>	Larger tread volume for longer mileage
 <p>Rationalized block stiffness distribution</p>	Excellent performance in irregular wear resistance
 <p>Open block design</p>	Effectively prevents occurrence of "heel & toe"
 <p>Open shoulder design</p>	Provides good traction performance with improved heat dissipation and endurance performance

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1759Q	16	H	148/145 L	8.25	7.50	6,940@123	6,395@120	11.0	19.3	41.5	30	501	138
295/75R22.5	100EV1675Q	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	18.9	40.4	30	514	129
11R24.5	COMING SOON	14	G	146/143 L	8.25	7.50	6,610@105	6,005@105	11.0	20.5	43.9	30	473	147
11R24.5	100EV1622Q	16	H	149/146 L	8.25	7.50	7,160@120	6,610@120	11.0	20.5	43.9	30	473	150
285/75R24.5	COMING SOON	14	G	144/141 L	8.25	—	6,175@110	5,675@110	11.1	19.6	41.8	30	497	137
<i>GT RADIAL GDR639: SEE PAGE 41 FOR MORE INFORMATION</i>														
11R22.5	100EV1499G	16	H	148/145 L	8.25	7.50	6,940@120	6,395@120	11.0	—	41.5	30	501	138
11R24.5	100EV1621G	16	H	149/146 L	8.25	7.50	7,160@120	6,610@120	11.0	—	43.9	30	473	148
285/75R24.5	100EV1477G	14	G	144/141 L	8.25	--	6,175@110	5,675@110	11.1	—	41.8	30	497	136

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES