



# GSR231 FS







All Position



Regional

## SmartWay Verified Regional All Position Tire

Features	Benefits
 Special compound with low heat generation & longer wear	Provides higher tire mileage and improved fuel economy
 Four groove design	Enhanced tread stiffness, reduce in rolling resistance, reliable control and handling
 Multiple sipes on ribs	Optimum traction & braking
 Optimized footprint distribution	Improves footprint performance to prevent irregular wear

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1782Q	14	G	144/142 L	8.25	7.5	6,175@105	5,840@105	11.0	19.3	41.5	21	501	132
11R22.5	100EV1991Q	16	H	148/145 L	8.25	7.5	6,940@123	6,395@123	11.0	19.3	41.5	21	501	132
11R24.5	COMING SOON	14	G	—	—	—	—	—	—	—	—	—	—	—
11R24.5	COMING SOON	16	H	—	—	—	—	—	—	—	—	—	—	—
295/75R22.5	100EV1674Q	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	18.6	39.9	21	521	123
<b>GT RADIAL GT279:</b> SEE PAGE 40 FOR MORE INFORMATION														
11R22.5	100EV611G	16	H	148/145 M	8.25	7.50	6,940@120	6,395@120	11.0	19.3	41.5	21	501	126
11R24.5	100EV682G	16	H	149/146 M	8.25	7.50	7,160@120	6,610@120	11.0	20.3	43.5	19	478	135
285/75R24.5	100EV761G	14	G	144/141 M	8.25	—	6,175@110	5,675@110	11.1	19.4	41.3	19	503	122

PR Ply Rating    LR Load Range    LI Load Index    SR Speed Rating    RPM Revolutions Per Mile

Giti manufactures SmartWay Verified Technologies. Learn more at [epa.gov/smartway](http://epa.gov/smartway).  
 Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES