



GDR639







For Trucks, Drive Position



Regional



Regional Drive Position Tire

Features	Benefits
 Modern open shoulder pattern	Excellent traction in a variety of regional applications
 Deeper groove depth	Extends long life
 Specific shoulder design	Provides excellent water evacuation and heat dispersion
 Wide footprint with square shoulders	Helps provide enhanced stability

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1499G	16	H	148/145 L	8.25	7.50	6,940@120	6,395@120	11.0	—	41.5	30	501	138
11R24.5	100EV1621G	16	H	149/146 L	8.25	7.50	7,160@120	6,610@120	11.0	—	43.9	30	473	148
285/75R24.5	100EV1477G	14	G	144/141 L	8.25	--	6,175@110	5,675@110	11.1	—	41.8	30	497	136

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

